

EBOX-333x Series, LAN x 2, RS-232, SATA

Model Type		EB-3330-L2SS	EB-3330-L2C1	EB-3330-L2C2	EB-3330-L2C3	EB-3330-L2C4
		EB-3332-L2SS	EB-3332-L2C1	EB-3332-L2C2	EB-3332-L2C3	EB-3332-L2C4
Processor		DM&P Vortex86DX2 (933MHz)				
BIOS		AMI BIOS				
Memory		Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series				
VGA		Integrated Graphics Chip/ D-Sub 15-pin				
Maximum Resolution		1920 x 1440 pixels				
Ethernet		10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)				
USB 2.0		External: 3 ports (Front x 2, Rear x 1) Internal: 1 port				
HD Audio		Line out				
I/O	SD Slot	1x				
	SATA	1x				
	COM1	N/A	RS-232	RS-232	RS-232	RS-232
	COM2		RS-232	RS-232	RS-232	
	COM3		N/A	RS-232	RS-232	
	COM4			N/A	RS-232	
Auto Power On		Yes				
Power		DC +8V~+24V				
Dimensions		115 x 115 x 35mm				
Unit Net Weight		510g				
Operation Temp.		5~50°C				
Certifications		CE, FCC, VCCI				
Optional		1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232 4. mPCIe (2.5" SATA HDD not support)				
Note		RS-232 COM ports in Full 9pin				

Features:

- DM&P Vortex86DX2 (933MHz)
- Onboard 1GB/ 2GB DDR2
- SATA DOM, 2.5" HDD, SSD support
- mSATA support (mSATA to SATA adapter required)
- SD, SDHC support
- VESA mounting support
- Fanless design
- 10/100 Mbps LAN x 1, 1 Gbps LAN x 1
- WiFi Dongle support (Optional)
- PXE Diskless Boot
- USB 2.0 port x 4
- RS-232 Up to 4 ports (Optional)
- Auto Power On support
- Ultra low power

